Performing an In-place Upgrade

Use this upgrade method to upgrade your existing NetWare[®] 3.1x or 4.x server to the NetWare 4.2 operating system (OS). Using install.nlm, you update your server with new OS and boot files, and, if necessary, upgrade the bindery to NDS.

PREREQUISITES

- □ Back up your NetWare 3.1*x* or 4.*x* system.
- □ If you are upgrading a NetWare 4.*x* server, check the ds.nlm version you are running. If it is earlier than 4.89, refer to Prepare the NDS Tree for Upgrade in Upgrade Using INSTALL.NLM of *Installation and Upgrade*.
- Copy the LAN drivers used by your server and server's autoexec.ncf file to floppy diskette.
- Bring down the server and copy all batch files, name spaces, device drivers, INSTALL.NLM, SERVER.EXE, STARTUP.NCF, and VREPAIR.NLM.
- Notify users to log out of the NetWare 3.1.x or 4.x server.

SYSTEM REQUIREMENTS

- □ NetWare 3.1x or 4.x server.
- NetWare 4.2 Operating System CD-ROM.
- CD-ROM drive installed on the server and the Operating System CD-ROM mounted as a NetWare volume, or the CD-ROM files copied to another server.

- Minimum of 20 MB of RAM on the server.
- Minimum of 175 MB Volume SYS on the server.
- □ Minimum 40 MB DOS partition.

PROCEDURE

 Change to the drive letter corresponding to your CD-ROM drive or the mapped drive where the NetWare 4.2 *Operating System* files are located and enter

install

- **2.** Select NetWare 4.2.
- **3.** Select Upgrade NetWare 3.1*x* or 4.*x*.
- 4. Follow the on-screen prompts.

||||**1**]